



Flow through a laboratory sediment sample by computer simulation modeling

R.B. Pandey^{a,b,*}, Allen H. Reed^a, Edward Braithwaite^a,
Ray Seyfarth^c, J.F. Gettrust^a

^aNaval Research Laboratory, Stennis Space Center, MS 39529, USA

^bDepartment of Physics and Astronomy, University of Southern Mississippi, Hattiesburg, MS 39406-5046, USA

^cSchool of Computing, University of Southern Mississippi, Hattiesburg, MS 39406-5106, USA

Received 20 May 2006; received in revised form 28 July 2006

Available online 7 September 2006

Abstract

A laboratory sediment sample is digitized by X-ray computed tomography system to obtain a host matrix of size 100^3 of porosity 0.282. Flow through the porous medium is studied by an interacting lattice gas model for fluid driven by pressure bias. The bias $H(0 \leq H \leq 1)$ is implemented via soft and hard pressure constraints in selecting the stochastic movement of fluid particles. The response of fluid flux density to bias H is nearly linear with soft pressure; it becomes nonmonotonic with the hard pressure.

© 2006 Elsevier B.V. All rights reserved.

Keywords: Porous medium formed by quartz sands; Interacting lattice gas; Computer simulation; Driven flow

Understanding the flow through porous media has attracted a considerable interest [1–4] for decades due to its complex response properties. Some applications include secondary oil recovery, spreading of spilled contaminants, and dissociation of gas (methane, carbon monoxide, etc.) in natural occurring processes [5]. Heterogeneous porous media for geomarine applications are generally modeled by percolation [6] and its variants. Transport and flow through such porous matrices have been extensively studied near and above the percolation threshold [7,8]. Scaling behavior of such response properties as the variation of the flux density with porosity, driving bias, temperature, etc. are relatively well understood. However, fluid flow through a laboratory sample [9,10] may differ from that in an idealized percolating porous matrix. Our goal is to understand realistic porous media and characterize its flow properties such as transport of fluid and hydraulic conductivity. The porous matrix is prepared in the laboratory from distribution of quartz sands with appropriate geomarine environmental conditions such as pressure, compaction, and temperature. Enormous efforts have been made in recent years to study structural patterns and flow of such granular materials in a variety of driving mechanisms such as vibrations, mixing, shearing, etc. by both computer simulations and

*Corresponding author. Department of Physics and Astronomy, University of Southern Mississippi, Hattiesburg, MS 39406-5046, USA. Tel.: +1 601 2664485; fax: +1 601 2665149.

E-mail address: ras.pandey@usm.edu (R.B. Pandey).

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 07092006	2. REPORT TYPE Journal Article	3. DATES COVERED (From - To)
---	-----------------------------------	------------------------------

4. TITLE AND SUBTITLE Flow through a laboratory sediment sample by computer simulation modeling	5a. CONTRACT NUMBER
	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S) R.B. Pandey, Allen H. Reed, Edward Braithwaite, Ray Seyfarth, J.F. Gettrust	5d. PROJECT NUMBER
	5e. TASK NUMBER
	5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory Marine Geoacoustics Division Stennis Space Center, MS 39529	8. PERFORMING ORGANIZATION REPORT NUMBER NRL/JA/7430-06-10
---	---

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research 800 North Quincy Street Arlington VA 22217-5000	10. SPONSOR/MONITOR'S ACRONYM(S) ONR
	11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited

13. SUPPLEMENTARY NOTES Physica A 374 (2007) 501-506	<h1>20090522022</h1>
---	----------------------

14. ABSTRACT Understanding the flow through porous media has attracted a considerable interest [1-4] for decades due to its complex response properties. Some applications include secondary oil recovery, spreading of spilled contaminants, and dissociation of gas (methane, carbon monoxide, etc.) in natural occurring processes [5]. Heterogeneous porous media for geomarine applications are generally modeled by percolation [6] and its variants. Transport and flow through such porous matrices have been extensively studied near and above the percolation threshold [7,8]. Scaling behavior of such response properties as the variation of the flux density with porosity, driving bias, temperature, etc. are relatively well understood. However, fluid flow through a laboratory sample [9,10] may differ from that in an idealized percolating porous matrix. Our goal is to

15. SUBJECT TERMS Porous medium formed by quartz sands; Interacting lattice gas; Computer simulation: Driven flow
--

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 6	19a. NAME OF RESPONSIBLE PERSON Allen Reed
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 228-688-5473

laboratory experiments [11–16]. We are focused on characterizing the flow through the network of pores formed from the granular sands, i.e., the laboratory sample, using a computer simulation model. Relatively few attempts [9] are made to carry out such studies of flow through such a laboratory porous medium. The distributions of sediments (barriers) and network of pores (pathways) in our laboratory sample are identified by X-ray computed tomography measurements. Using a digitized image of the sample as a host matrix, attempts are made to characterize its flow properties and hydraulic conductivity via an interacting lattice gas method.

We consider a cubic lattice of size L^3 with $L = 100$, the digitized laboratory sample with a source of fluid particles connected to the bottom of the lattice ($z = 1$). The sediment sites act as impenetrable immobile barriers while the nearest-neighbor pore sites attract the mobile hard-core fluid particles. The interaction energy between a particle and its adjacent pore site is taken to be $J = -1$. The molecular weight of fluid constituents ($M = 0.1$, relatively small here) facilitates the downward ($-z$) fall and resist the upward ($+z$) move via change in the gravitational potential energy ($M\Delta z$, $\Delta z = \pm 1$). The change in energy (interaction and gravitational) is used in the Boltzmann distribution at a fixed temperature ($T = 1$) in implementing the move by the Metropolis algorithm. The source of fluid particles at the bottom creates a high concentration gradient which drives the particles upward against gravity. Additionally, we consider hydrostatic pressure bias (H) to drive these constituents upward (follows).

Selection of an adjacent neighboring site along the transverse ($\pm x, \pm y$) and vertical ($\pm z$) directions for a particle's move depends on the bias. Three types of bias are considered with $0 \leq H \leq 1$ which could be used to describe different scenario as explained briefly below.

I: Hopping probability along the transverse directions remains independent of bias which controls only the longitudinal moves. The bias along the longitudinal direction decreases with the height (z) with a linear gradient.

$$P_x = P_{-x} = P_y = P_{-y} = \frac{1}{6}, \quad P_{-z} = \frac{1 - H[1 - (z/L)]}{6}, \quad P_z = \frac{1 + H[1 - (z/L)]}{6}. \quad (1)$$

The bias is linear with the height z with the largest at $z = 0$. Even at the largest value of bias, $H = 1$, the maximum hopping probability along z -direction cannot exceed $\frac{1}{3}$. Since the selection of nearest-neighbor site for hopping along the transverse directions ($\pm x, \pm y$) remain independent of bias, it is not feasible to implement extreme bias that can channel fluid flow only along one direction.

II: The hopping along the longitudinal direction depends on the bias but becomes independent of the height while maintaining the constant hopping rate along the transverse directions.

$$P_x = P_{-x} = P_y = P_{-y} = \frac{1}{6}, \quad P_{-z} = \frac{1 - H}{6}, \quad P_z = \frac{1 + H}{6}. \quad (2)$$

III: Hopping along all directions are coupled with bias such that at extreme value of the bias ($H \rightarrow 1$), probability of selecting a hopping site along the positive longitudinal direction approaches one and zero along the rest.

$$P_x = P_{-x} = P_y = P_{-y} = P_{-z} = \frac{1 - H}{6}, \quad P_z = \frac{1 + 5H}{6}. \quad (3)$$

With this bias, one can examine a much larger range in channeling the flow. Thus, with these three bias one should be able to study flow in a large pool of systems.

To implement the hopping [7,8], we select a particle say at a lattice site i randomly. One of its six nearest-neighbor sites say j is selected with above probability. If site j is empty then an attempt is made to move the particle from site i to site j with the Metropolis algorithm. Periodic boundary conditions are used along the transverse direction; both the top ($z = L$) and the bottom ($z = 1$) of the sample are open for particles to escape. A particle is released from the source into a bottom lattice site as soon as it is vacated by the particle when it moves up or diffuses laterally. As usual, attempts to move each particle once define the unit Monte Carlo step (MCS) time. As the simulation proceeds, particles move in and out of the sample. The number of particles and their concentration profiles (planar densities along x, y, z) change but eventually reach a steady-state—a non-equilibrium steady-state system. Simulations are performed with many independent initial configurations but with the same host matrix, each for a sufficiently long time steps to reach steady-state.




Fig. 1. Distribution of pores in the sample 100^3 from quartz sand grains (see Fig. 2 for details).

The laboratory sample is relatively dense with a fraction of sediment barriers $p_b = 0.718$ and pore sites $p_o = 0.282$. Thus, it would be better to look at the porous medium with empty sites of the sample. Fig. 1 shows the distribution of pores in the digital sample. Note that the fraction of pore sites is below the site percolation threshold ($p_c \simeq 0.3117$) [6], yet we have connected pathway of pores that span the entire sample. Obviously, open channels in the real sample are different from the idealized percolating matrix with random distribution of barriers in a site percolation. To depict the contrast and complementarity in distribution of sediments and pores, in Fig. 2 we present a slice of the sample with distribution of its sediment and pore sites.

We perform the computer simulation experiment by injecting fluid at one end and monitoring its net flux rate from the opposite end by varying the bias for three types of driving mechanisms described above. During the simulation, we also keep track of the root mean square (rms) displacement of each particle (tracer) and their center of mass, density profiles, and flux of fluid. Fig. 3 shows the variation of the rms displacement with the time steps (t) for a range of bias values with pressure bias III. We see that particles, individually (tracer) and collectively (center of mass) drift, i.e., $R \propto t$, in the long time (asymptotic) regime. Such an asymptotic drift behavior is expected in the long time regime for our driven system due to pressure bias and concentration gradient. Note that the asymptotic drift behavior also suggests that the system has reached its steady-state which is verified by the analysis of flux density in the following.

There is a net mass transfer due to net driving field (along $+z$ direction) caused by (1) the concentration gradient developed by the source at the bottom and (2) the pressure bias. Fluid particles enter at the bottom and leave mostly from the top. The amount of fluid entering the system must be equal to amount leaving in the steady-state due to conservation of mass, i.e., the continuity equation. The fluid current i can be estimated




Fig. 2. Distribution of sediment (left) and pores (right) in slices of equal thickness at $z = 21\text{--}40$ in the sample which is prepared from quartz sand grains. The sandy sediments are collected from surficial marine deposits. Sediments are subrounded to subangular in shape have a mean grain size or d_{50} of 0.375 mm and serve as the boundaries for the pores (right).




Fig. 3. Variation of the root mean square displacement of each particle (tracer), R_t and their center of mass (right), R_c , with bias III on sample shown in Fig. 1.

from the rate of net mass (Q) transfer,

$$i = \frac{dQ}{dt}. \quad (4)$$

The current or flux density (j) is the current per unit cross-sectional area (A_C),

$$j = i/A_C. \quad (5)$$

The flux density is linearly proportional to hydraulic conductivity (κ) for flow with linear response (with $\delta = 1$),

$$j = \kappa H^\delta. \quad (6)$$




Fig. 4. Variation of the mass flux density rate (left) and longitudinal (along bias) density profile with bias III.




Fig. 5. Variation of the steady-state value of flux density with bias H for three types I, II, III.

Variation of the flux density with the time step is presented in Fig. 4 for the entire range of a bias (III). We see that the flux density reaches its constant value rather fast. Corresponding density profiles are also shown in this figure. The non-linear density profiles are mostly due to morphology of the pore distribution except at extreme bias $H = 1$. Movement of fluid particles ceases as they are trapped against sediment barrier at the extreme value of type III bias.

Response of the flux density to the bias can be analyzed by examining the variation of its steady-state value with the bias. Fig. 5 shows the variation for three types of pressure bias. For bias I and II, we see relatively

linear responses of the flux density to bias while for bias III, a non-monotonic dependence is observed. Note that in case of bias I and II, the hopping probability of fluid constituents along the transverse directions never ceases even at extreme values of the bias. With the pressure bias III, the movement in all directions except z ceases at $H = 1$. We believe that the implementation of the pressure bias III is more realistic in directing the flow which shows a non-monotonic response of the flux density. We are in a process to carry out both laboratory and computer simulation experiments simultaneously to see which bias is more appropriate in describing the flow properties of the porous sediment.

We acknowledge partial support from ONR PE # 0602435N and NSF-EPSCoR grants. This work was supported in part by grants of computer time from the DOD High Performance Computing Modernization Program at the Major Shared Resource Center (MSRC), NAVO, Stennis Space Center.

References

- [1] V.I. Selyakov, V.V. Kadet, *Percolation Models for Transport in Porous Media: With Applications to Reservoir Engineering*, Springer, Berlin, 1997.
- [2] J.M. Crolet (Ed.), *Computational Methods for Flow and Transport in Porous Media*, Springer, Berlin, 2000.
- [3] B. Loret, J.M. Huyghe (Eds.), *Chemo-Mechanical Couplings in Porous Media Geomechanics and Biomechanics*, Springer, Berlin, 2004.
- [4] P. Grathwohl, *Diffusion in Natural Porous Media: Contaminant Transport. Sorption/Desorption and Dissolution Kinetics*, Springer, Berlin, 1998.
- [5] Proceeding of the Fourth International Conference on Gas Hydrate, Yokohama, 2002.
- [6] D. Stauffer, A. Aharony, *Introduction to Percolation Theory*, second ed., Taylor & Francis, London, 1994.
- [7] R.B. Pandey, J.F. Gettrust, D. Stauffer, *Physica A* 300 (2001) 1.
- [8] R.B. Pandey, J. Becklehimer, J.F. Gettrust, *Physica A* 289 (2001) 321.
- [9] M. Turner, L. Knuefing, C.H. Arns, A. Sakellariou, T.J. Senden, A.P. Sheppard, R.M. Sok, L. Limaye, W.V. Pinczewski, M.A. Knackstedt, *Physica A* 339 (2004) 166.
- [10] A.H. Reed, R.B. Pandey, D.L. Lavoie, *Int. J. Mod. Phys. C* 11 (2000) 1555.
- [11] A. Mehta (Ed.), *Granular Matter: An Interdisciplinary Approach*, Springer, New York, 1994.
- [12] A. Coniglio, A. Fierro, H.J. Herrmann, M. Nicodemi (Eds.), *Unifying Concepts in Granular Media and Glasses*, Elsevier, Amsterdam, 2004.
- [13] H.A. Makse, S. Havlin, P.R. King, H.E. Stanley, in: L. Schimansky-Geier, T. Poeschel (Eds.), *Novel Pattern Formation in Granular Matter*, Springer, Heidelberg, 1997, p. 319.
- [14] M. Latzel, S. Luding, H.J. Herrmann, *Granular Matter* 2 (2000) 123.
- [15] R. Consiglio, D.R. Baker, G. Paul, H.E. Stanley, *Physica A* 319 (2003) 49.
- [16] J. Geng, R.P. Behringer, *Phys. Rev. Lett.* 93 (2004) 238002.